

PRODUCT SPECIFICATION

Part Name / 产品型号	Plastic Screw Protective Vent
Voir P/N / 沃瑞编码	VV-POVM08P3A-D10
Customer / 客户型号	
Customer P/N / 客户料号	
Issue Date / 发布日期	2015-3-26

Checked / 审核		Prepared / 制作			
Li Zuo jun		Zeng Zhi			
Customer Approve / 客户核准					
_					
_					

地址:广东省惠州市仲恺高新区54号小区和畅东4路 网址: www.voir-tech.com.cn 电话: +86 400-6136683 传真: +86 752-5310696

ADD: Hechang Road East 4 NO. 54 Ares, Zhongkai New and High-tech Industries Development Zone, Huizhou City Guangdong Province, Chine Http://www.voir-tech.com.cn TEL: +86 400-6136683 FAX:+86 752-5310696

Component				
Body	PC			
Membrane	E-PTFE			
Ring	Silicone			
Parameter				
Airflow	134ml/min at Δp=1.25mbar			
WEP	>40Kpa			
Temperature	-40°C∼ 125°C			
IP Rate	IP68			

1. Vents in high airflow to balance the pressure and lower down tension for sealing stripe.

Benefits to Outdoor Equipment

- 2. With the hydrophobic and oleophobic membrane inserted inside the anodized aluminum body, the vent plug becomes chemically inner and UV-resistant.
- 3. Press-fit installation and the silica sealing ring can both help in enhancing the airtightness.




M08P3A protective vent. M08*1.0 threaded, is made of PC with microporous structure e-PTFE membrane welded inside the body to make it liquid barrier while being air permeable. It is ROHS compliant with strong UV/ salt fog resistance. After tests, it reaches IP68 and wide range of application.


Application:

Applicable for industrial dust-collector and packing container, cosmetic and medicine industrial, household application, LED, communication equipment, solar equipment and automotive components. Not applicable for highly corrosive and acid-base environment


Practical Principle



Detailed Spec.



Installation Suggestion



Specification

SKU#	Material	Diameter/mm	Airflow/WEP
VV POVM08 P3A-D10	PC	M08*1.0	A/P:134ml/min @1.25mbar WEP:>40kpa

H-housing thickness, ø-hole diameter; torsion: 0.9N/m

- 1. When H>3mm, it is suggested to drill a M08*1.0 threaded hole. Chamfer is need for O-ring, please refer to Suggestion 1
- 2. When H<3mm, it is suggested to drill a Ø8.2mm straight hole and lock with nut. Chamfer is not needed for Flat-ring, please refer to Suggestion 2

传真: +86 752-5310696

Customization: VoirTech's protective vents can be customized to match your products in spec., color, property and even provide specific solution. For more information, please contact us.



网址: www.voir-tech.com.cn

电话: +86 400-6136683

ADD: Hechang Road East 4 NO. 54 Ares, Zhongkai New and High-tech Industries Development Zone. Huizhou City Guangdong Province, Chine Http: www. voir-tech. com. cn

TEL: +86 400-6136683 FAX:+86 752-5310696