


PRODUCT PHOTO



SPECIFICATIONS

- Economic one-piece solution
- No need of any AC to DC driver. Direct plug to 200~240V 50/60 Hz AC supply
- Emergency Kit feature with external battery (Niced or Li-on Battery)
- Suits downlight, wall, corridor, applique lighting and especially emergency exit area
- Provide less weight mechanical structure
- Highest Efficacy ($> 125 \text{ lm/W}$)
- Longer Life Span (50.000h)
- Higher Power Factor (> 0.97)
- Low THD $< \%20$
- EMC tested compatible with EN55015
- Withstand High Surge & Burst L-N : 2KV (EN 61000-4-5 Class 3)
- Compatibility of ROHS and CE
- Microprocessor controlled constant power mode independents of line voltage
- CRI 80 is standart, CRI 70 and CRI 90 are available
- Easy installation, no need to worry for driver spac



For your orders please call us:

+90 444 27 33


APPLICATIONS



Downlight

Indoor

PHOTOMETRY




X-MR00185NC-NFSx757G-V1-AC42 with EMG Kit

DATASHEET

X-MR00185NC-NFSx757G-V1-AC42 with EMG Kit

Low Coast AC DC Module with Emergency Kit



SERBEST ÖLÇÜ TOLERANSLARI - DIN 2768-1 / General Tolerances for linear and angular dimensions (DIN ISO 2768-1)

0.5 up to 3mm	± 0.1	over 3 up to 6mm	± 0.1	over 6 up to 30mm	± 0.2	over 30 up to 120mm	± 0.3	over 120 up to 400mm	± 0.5	over 400 up to 1000mm	± 0.8
---------------	-------	------------------	-------	-------------------	-------	---------------------	-------	----------------------	-------	-----------------------	-------

Stock code No :	MALZEME (MATERIAL)		AGIRLIK (WEIGHT)		 Ölçek / SCALE	A4
Revision : 00	PC					
Date: 02.02.2017	PARÇA NO (PART NO)				 TD Lighting Solutions	
Sheet : 1						
Drawn By : M. KAZAKLI						
Checked By : D. SANATSEVER						
Approved By : M. CINAR						

TLS Teknoloji Sanayi ve Ticaret A.Ş. This drawing is our property. It can't be reproduced or communicated without our written agreement.

