




TD Lighting Solutions




X-MR0095NCxx-NF2W757GRV3-39-E200-20W

Linear Series

www.tlsteknoloji.com

PRODUCT PHOTO



SPECIFICATIONS

- No need of any AC to DC driver
- Direct plug to 200~240V 50/60 Hz AC supply
- Highly Cost Effective
- Suits wall and ceiling lights
- Provide less weight mechanical structure
- Highest Efficacy (> 125 lm/W)
- Longer Life Span (50.000h)
- Higher Power Factor (> 0.97)
- Low THD <%20
- EMC tested compatible with EN55015
- Withstand High Surge & Burst L-N : 2KV (EN 61000-4-5 Class 3)
- Compatibility of ROHS and CE
- Microprocessor controlled constant power mode independents of line voltage
- CRI 80 is standart, CRI 70 and CRI 90 are available
- Easy installation, no need to worry for driver spac



For your orders please call us:
+90 444 27 33

APPLICATIONS



Downlight




Indoor



Office Lighting

PHOTOMETRY



TECHNICAL SPECS

Rated Voltage	220-240 V AC
Input Voltage	198-260 V AC
Frequency	47-63 Hz
PF	>0,97
Ambient Temp.	-20 ~+50°C 20-90% RH
Max. Case Temp.	85 °C
Beam Angle	120°
IP Level	IP00
Dimintions	Ø 95 mm

PHOTOMETRIC MEASUREMENTS (LM-79-08)

Module Lumen Output	2525lm +/-%5
Module Power	20W
Module Efficiency	> 125lm/W
CRI	>80

ABSOLUTE MAXIMUM RATING Ta=25 °C


PARAMETER	SYMBOL	UNIT	VALUE
Maximum Input Voltage	Vin	Vac	265V AC
Power Consumption	P	W	20W
Operation Temperature	Topr	°C	- 30 ~ 85
Storage Temperature	Tstg	°C	- 40 ~ 100
ESD Sensivity			2KV

The table below shows how to Module Light Output changes depending on CCT (°K)



	Lumen Output Multiplier				
	2700°K (CRI 80)	3000°K (CRI 80)	4000°K (CRI 80)	5000°K (CRI 80)	6500°K (CRI 80)
NF2W757GR-V3-R8000	0,875	0,916	1	1	1

Relative luminous intensity versus CCT (°K)

X-MR0095NCxx-NF2W757GRV3-39-E200-20W MECHANICAL DRAWINGS




SERBEST ÖLÇÜ TOLERANSLARI -DIN 2768-1 / General Tolerances for linear and angular dimensions (DIN ISO 2768-1)

0.5 up to 3mm		over 3 up to 6mm		over 6 up to 30mm		over 30 up to 120mm		over 120 up to 400mm		over 400 up to 1000mm	
± 0.1		± 0.1		± 0.2		± 0.3		± 0.5		± 0.8	
Stock code No				MALZEME (MATERIAL) XXX		AGIRLIK (WEIGHT) XXX					
Revision	00										
Date	10.12.2019								OLÇEK / SCALE		A4
Sheet											
Drawn By	Kaan ALTINTEN										
Checked By	Ibrahim OKMEN										
Approved By	Mesut CINAR										

TLS Teknoloji Sanayi ve Dis Ticaret A.S

This drawing is our property. It cant be reproduced or communicated without our written agreement.

CCT AND BINNING INFORMATION



LEGAL NOTICE

Product information provided by TLS Teknoloji Sistemleri San ve Dış Tic AŞ ("TLS") in this document is believed to be correct and accurate. TLS reserves the right to change/correct the specifications and other data or information relating to products without notice but TLS accepts no liability for errors that may appear in this document, howsoever occurring, or liability arising from the use or application of any information or data provided herein. Neither the supply of such information, nor the purchase or use of products conveys any licence or permission under patent, copyright, trademark or other intellectual property right of TLS or third parties.

Products sold by TLS are subject to its standard Terms and Conditions of Sale that are available on request. No warranty is given that products do not infringe the intellectual property rights of third parties, and furthermore, the use of products in certain ways or in combination with TLS, or non-TLS furnished equipments/components may infringe intellectual property rights of TLS.

The purpose of this document is to provide information only and it may not be used, applied or reproduced (in whole or in part) for any purpose nor be taken as a representation relating to the products in question. No warranty or guarantee express or implied is made concerning the capability, performance or suitability of any product, and information concerning possible applications or methods of use is provided for guidance only and not as a recommendation. The user is solely responsible for determining the performance and suitability of the product in any application and checking that any specification or data it seeks to rely on has not been superseded.

Products are intended for normal commercial applications. For applications requiring unusual environmental requirements, extended temperature range, or high reliability capability (e.g. military, or medical applications), special processing/testing/conditions of sale may be available on application to TLS.

CONTACT

TLS Teknoloji Sistemleri San ve Dış Tic AŞ

Akçaburgaz Mahallesi 3080. Sokak No:5 Esenyurt / İstanbul / TURKEY

info@tsteknoloji.com
+90 444 27 33