


PRODUCT PHOTO



SPECIFICATIONS

- Default driving method is constant current input
- CCT Range from 2700K up to 6500K
- This module can be used as 24 series 1 parallels.
- Luminous flux range from 4922 lm to 7544 lm
- Efficacy of the module up to 166 lm/W
- CRI 70 is standard.CRI 80 and CRI 90 is available.
- Outstanding system color tolerance MacAdam 3 over the full operating area
- Simple installation (e.g. screw)
- Long life-time > 60,000 hours
- 5 years guarantee at specified conditions



For your orders please call us:


+90 444 27 33

APPLICATIONS



Street Lighting

PHOTOMETRY




TLS08NI-5050-STL-M2M3

TECHNICAL DATA

Beam Angle	120°
Ambient temperature range	-25° ~ +55°C
Tc max	100°C
Max. DC forward current	700mA
Typical voltage of LED Module at max current	69 V
Insulation test voltage	2kV
ESD classification	Class 1
Risk group (EN 62471:2008)	2
Type of protection	IP00

ORDERING INFORMATION



DRIVING CURRENT VS LUMEN OUTPUT SPECIFICATION


Common Characteristic [@Tj : 85°C] ;			
Module Code	X-MS100112NCxx-NVSW219F-24		
PCB Material	ALU	Electrical Connection	
Operating Temperature (°C)	-40 ~ +100	Parallel	1
Storage Temperature (°C)	-40 ~ +55	Series	24
Thermal Conductivity (W/m-K)	1>	LED Quantity	24
LED NVSW219F-V1_R8000			
Correlated Color Temperature (CCT)	4000K		
Color Rendering Index (CRI)	80+		
Module Operating Voltage (V)	67	68	69
Module Operating Current (mA)	500	700	700
Branch Operating Current (mA)	500	600	700
Module Power (W)	33,48	47,54	48,05
Module Light Output (lm)	4.922	6.799	6727
Module Efficiency (lm/W)	147	143	140
LED NVSW219F_R70			
Correlated Color Temperature (CCT)	4000K		
Color Rendering Index (CRI)	70+		
Module Operating Voltage (V)	67	68	69
Module Operating Current (mA)	500	600	700
Branch Operating Current (mA)	500	600	700
Module Power (W)	33,48	40,75	48,05
Module Light Output (lm)	5.558	6.561	7544
Module Efficiency (lm/W)	166	161	157

The table below shows how to Module Light Output changes depending on CCT (°K)


Lumen Output Multiplier					
LED	2700°K (CRI 80)	3000°K (CRI 80)	4000°K (CRI 80)	5000°K (CRI 80)	6500°K (CRI 80)
NVSW219F-V1_R8000	0,88	0,92	0,96	0,97	0,94

Lumen Output Multiplier					
LED	2700°K (CRI 70)	3000°K (CRI 70)	4000°K (CRI 70)	5000°K (CRI 70)	6500°K (CRI 70)
NVSW219F_R70	0,93	0,95	1,00	1,01	X

Relative luminous intensity versus CCT (°K)



CCT AND BINNING INFORMATION



LIFE TIME

MODEL NUMBER: NVSW219F



Report No. : SQETMS534401

LM-80 Test Report

This LM-80 testing is performed in accordance with IES LM-80-15.

Part No. NVSW219F

Issue Date: November 4, 2020 **Revision Date:** -
Test Initiation Date: March 29, 2018 **Test Completion Date:** June 19, 2020
Test Duration: 10,000 hours **Report No.:** SQETMS534401

Customer Information:

Company Name: Nichia Corporation
Address: 491-100, Oka, Kaminaka-cho, Anan-shi, Tokushima, 774-8601, JAPAN

Description of Test Samples:

Manufacturer's Name: Nichia Corporation
Classification: LED Package
Part Name: White LED
Part No.: NVSW219F
Nominal CCT: 2700 K

Test Summary:

Data Set	Case Temperature [°C]	Ambient Temperature [°C]	Drive Current [mA]	Luminous Flux Maintenance at 10K hours [%]	Chromaticity Shift ($\Delta u'v'$) at 10K hours	TM-21 Projection $L_{50}(10K)$ [hours]	TM-21 Projection $L_{50}(10K)$ [hours]	TM-21 Projection $L_{50}(10K)$ [hours]
1	55	> 50	700	98.6	0.0005	> 60000	> 60000	> 60000
2	55	> 50	1500	97.6	0.0007	> 60000	> 60000	> 60000
3	85	> 80	700	98.3	0.0005	> 60000	> 60000	> 60000
4	85	> 80	1200	97.7	0.0010	> 60000	> 60000	> 60000
5	85	> 80	1500	96.9	0.0015	> 60000	> 60000	> 60000
6	105	> 100	700	97.6	0.0007	> 60000	> 60000	> 60000
7	105	> 100	1200	95.8	0.0019	> 60000	> 60000	32100
8	105	> 100	1500	83.6	0.0019	15200	11200	7720 *

* The L_p value is reached experimentally in the course of LM-80 testing.

Approved Signatory:

Takara WAKAKI, Lab Manager

Nichia Corporation LED Testing Laboratory

1-1, Tatsumi-cho, Anan-shi, TOKUSHIMA 774-0001, JAPAN

The certificate shall not be reproduced, except in full, without written approval of the laboratory.

The laboratory is accredited in accordance with the recognized International Standard ISO/IEC 17025:2017.

LEGAL NOTICE

Product information provided by TLS Teknoloji Sistemleri San ve Dış Tic AŞ ("TLS") in this document is believed to be correct and accurate. TLS reserves the right to change/correct the specifications and other data or information relating to products without notice but TLS accepts no liability for errors that may appear in this document, howsoever occurring, or liability arising from the use or application of any information or data provided herein. Neither the supply of such information, nor the purchase or use of products conveys any licence or permission under patent, copyright, trademark or other intellectual property right of TLS or third parties.

Products sold by TLS are subject to its standard Terms and Conditions of Sale that are available on request. No warranty is given that products do not infringe the intellectual property rights of third parties, and furthermore, the use of products in certain ways or in combination with TLS, or non-TLS furnished equipments/components may infringe intellectual property rights of TLS.

The purpose of this document is to provide information only and it may not be used, applied or reproduced (in whole or in part) for any purpose nor be taken as a representation relating to the products in question. No warranty or guarantee express or implied is made concerning the capability, performance or suitability of any product, and information concerning possible applications or methods of use is provided for guidance only and not as a recommendation. The user is solely responsible for determining the performance and suitability of the product in any application and checking that any specification or data it seeks to rely on has not been superseded.

Products are intended for normal commercial applications. For applications requiring unusual environmental requirements, extended temperature range, or high reliability capability (e.g. military, or medical applications), special processing/testing/conditions of sale may be available on application to TLS.

CONTACT

TLS Teknoloji Sistemleri San ve Dış Tic AŞ

Akçaburgaz Mahallesi 3080. Sokak No:5 Esenyurt / İstanbul / TURKEY

info@tsteknoloji.com
+90 444 27 33