


TECHNICAL DATA

Beam Angle	120°
Ambient temperature range	-25° ~ +55°C
Tc max	100°C
Max. DC forward current	1400mA
Typical voltage of LED Module at max current	103 V
Insulation test voltage	2kV
ESD classification	Class 1
Risk group (EN 62471:2008)	2
Type of protection	IP00

ORDERING INFORMATION



DRIVING CURRENT VS LUMEN OUTPUT SPECIFICATION


Common Characteristic [@Tj : 85°C] ;			
Module Code	X-MS150162NCxx-NVSW219F-72		
PCB Material	ALU	Electrical Connection	
Operating Temperature (°C)	-40 ~ +100	Parallel	2
Storage Temperature (°C)	-40 ~ +55	Series	36
Thermal Conductivity (W/m-K)	1>	LED Quantity	72
LED NVSW219F-V1_R8000			
Correlated Color Temperature (CCT)	4000K		
Color Rendering Index (CRI)	80+		
Module Operating Voltage (V)	100	102	103
Module Operating Current (mA)	1000	1200	1400
Branch Operating Current (mA)	500	600	700
Module Power (W)	100,44	122,26	144,14
Module Light Output (lm)	14.765	17.483	20180
Module Efficiency (lm/W)	147	143	140
LED NVSW219F_R70			
Correlated Color Temperature (CCT)	4000K		
Color Rendering Index (CRI)	70+		
Module Operating Voltage (V)	100	102	103
Module Operating Current (mA)	1000	1200	1400
Branch Operating Current (mA)	500	600	700
Module Power (W)	100,44	122,26	144,14
Module Light Output (lm)	16.673	19.683	22631
Module Efficiency (lm/W)	166	161	157

The table below shows how to Module Light Output changes depending on CCT (°K)


Lumen Output Multiplier					
LED	2700°K (CRI 80)	3000°K (CRI 80)	4000°K (CRI 80)	5000°K (CRI 80)	6500°K (CRI 80)
NVSW219F-V1_R8000	0,88	0,92	0,96	0,97	0,94

Lumen Output Multiplier					
LED	2700°K (CRI 70)	3000°K (CRI 70)	4000°K (CRI 70)	5000°K (CRI 70)	6500°K (CRI 70)
NVSW219F_R70	0,93	0,95	1,00	1,01	X

Relative luminous intensity versus CCT (°K)




SERBEST ÖLÇÜ TOLERANSLARI -DIN 2768-1 / General Tolerances for linear and angular dimensions (DIN ISO 2768-1)

0.5 up to 3mm	over 3 up to 6mm	over 6 up to 30mm	over 30 up to 120mm	over 120 up to 400mm	over 400 up to 1000mm
± 0.1	± 0.1	± 0.2	± 0.3	± 0.5	± 0.8
Stock code No		MALZEME (MATERIAL)	AGIRLIK (WEIGHT)		
Revision	00	XXX	XXX		
Date	21.06.2021	TLS-10S162150NC35-72-T1.6			OLÇEK / SCALE
Sheet					A4
Drawn By	Kaan ALTINTEN				 TD Lighting Solutions
Checked By	Kaan ALTINTEN				
Approved By	Utku OZTURK				

TLS Teknoloji Sanayi ve Dis Ticaret A.S

This drawing is our property. It cant be reproduced or communicated without our written agreement.

CCT AND BINNING INFORMATION



LIFE TIME

MODEL NUMBER: NVSWF219F



Report No. : SQETMS534401

LM-80 Test Report

This LM-80 testing is performed in accordance with IES LM-80-15.

Part No. NVSW219F

Issue Date: November 4, 2020 **Revision Date:** -
Test Initiation Date: March 29, 2018 **Test Completion Date:** June 19, 2020
Test Duration: 10,000 hours **Report No.:** SQETMS534401

Customer Information:

Company Name: Nichia Corporation
Address: 491-100, Oka, Kaminaka-cho, Anan-shi, Tokushima, 774-8601, JAPAN

Description of Test Samples:

Manufacturer's Name: Nichia Corporation
Classification: LED Package
Part Name: White LED
Part No.: NVSW219F
Nominal CCT: 2700 K

Test Summary:

Data Set	Case Temperature [°C]	Ambient Temperature [°C]	Drive Current [mA]	Luminous Flux Maintenance at 10K hours [%]	Chromaticity Shift ($\Delta u'v'$) at 10K hours	TM-21 Projection $L_{50}(10K)$ [hours]	TM-21 Projection $L_{50}(10K)$ [hours]	TM-21 Projection $L_{50}(10K)$ [hours]
1	55	> 50	700	98.6	0.0005	> 60000	> 60000	> 60000
2	55	> 50	1500	97.6	0.0007	> 60000	> 60000	> 60000
3	85	> 80	700	98.3	0.0005	> 60000	> 60000	> 60000
4	85	> 80	1200	97.7	0.0010	> 60000	> 60000	> 60000
5	85	> 80	1500	96.9	0.0015	> 60000	> 60000	> 60000
6	105	> 100	700	97.6	0.0007	> 60000	> 60000	> 60000
7	105	> 100	1200	95.8	0.0019	> 60000	> 60000	32100
8	105	> 100	1500	83.6	0.0019	15200	11200	7720 *

* The Lp value is reached experimentally in the course of LM-80 testing.



Approved Signatory:

Takara WAKAKI, Lab Manager

Nichia Corporation LED Testing Laboratory
 1-1, Tatsumi-cho, Anan-shi, TOKUSHIMA 774-0001, JAPAN

The certificate shall not be reproduced, except in full, without written approval of the laboratory.
 The laboratory is accredited in accordance with the recognized International Standard ISO/IEC 17025:2017.

LEGAL NOTICE

Product information provided by TLS Teknoloji Sistemleri San ve Dış Tic AŞ ("TLS") in this document is believed to be correct and accurate. TLS reserves the right to change/correct the specifications and other data or information relating to products without notice but TLS accepts no liability for errors that may appear in this document, howsoever occurring, or liability arising from the use or application of any information or data provided herein. Neither the supply of such information, nor the purchase or use of products conveys any licence or permission under patent, copyright, trademark or other intellectual property right of TLS or third parties.

Products sold by TLS are subject to its standard Terms and Conditions of Sale that are available on request. No warranty is given that products do not infringe the intellectual property rights of third parties, and furthermore, the use of products in certain ways or in combination with TLS, or non-TLS furnished equipments/components may infringe intellectual property rights of TLS.

The purpose of this document is to provide information only and it may not be used, applied or reproduced (in whole or in part) for any purpose nor be taken as a representation relating to the products in question. No warranty or guarantee express or implied is made concerning the capability, performance or suitability of any product, and information concerning possible applications or methods of use is provided for guidance only and not as a recommendation. The user is solely responsible for determining the performance and suitability of the product in any application and checking that any specification or data it seeks to rely on has not been superseded.

Products are intended for normal commercial applications. For applications requiring unusual environmental requirements, extended temperature range, or high reliability capability (e.g. military, or medical applications), special processing/testing/conditions of sale may be available on application to TLS.

CONTACT

TLS Teknoloji Sistemleri San ve Dış Tic AŞ

Akçaburgaz Mahallesi 3080. Sokak No:5 Esenyurt / İstanbul / TURKEY

info@tsteknoloji.com
+90 444 27 33